


10K

SWING CHECK VALVE

Pressure-Temperature Rating: 1.0MPa: 180°C



Parts	UOB	UOBM
Body	SCS13A	SCS14A
Cap	SCS13A/SUS304	SCS14A/SUS316
Disc	SCS13A	SCS14A
Hinge pin	SUS304	SUS316
Plug	SUS304	SUS316
Gasket (for plug)	Asbestos-free sheet	

Face-to-Face Dimensions: JIS B2011 *Except flange thickness.
End Flange Dimensions: JIS B2220*
Wall Thickness: KITZ Std.

UOB


UOBM

Nominal Size	Unit:mm							
	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	85	95	110	130	150	180	210	240
H	45	55	61	71	72	81	95	105

TYPE 200

SWING CHECK VALVE

Pressure-Temperature Rating: 1.0MPa: 180°C
200psi. W.O.G.: 350°F S.P.



Parts	AKUOM
Body	CF8M
Cap	CF8M/316
Disc	CF8M
Hinge pin	316
Plug	316
Gasket (for plug)	Aramid fiber

Face-to-Face Dimensions: KITZ Std.
End Thread Dimensions: ASME B1.20.1
Wall Thickness: KITZ Std.


AKUOM

Nominal Size	Unit:mm							
	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
L	65	80	90	105	120	140	180	200
H	45	55	61	71	72	81	93	104

10K

LIFT CHECK VALVE

Pressure-Temperature Rating: 1.0MPa: 180°C



Parts	UN
Body	SCS13A
Cap	SCS13A/SUS304
Disc	SUS304

Face-to-Face Dimensions: JIS B2011
End Thread Dimensions: JIS B0203
Wall Thickness: KITZ Std.

UN

Nominal Size	Unit:mm						
	3/8	1/2	3/4	1	1 1/4	1 1/2	2
L	55	65	80	90	105	120	140
H	50	53	54	62	66	76	85